



#### Standard hjørne stolpe

122 mm karm - 60x60 mm.  
149 mm karm - 75x75 mm.  
175 mm karm - 100x100 mm.  
210 mm karm - 125x125 mm.

Opklodsning, skrueafstande og -placering som standard montage.

#### Standard corner post

122 mm frame - 60x60 mm.  
149 mm frame - 75x75 mm.  
175 mm frame - 100x100 mm.  
210 mm frame - 125x125 mm.

Wedging, fixing points and fixing areas as standard installation.

#### Alternativ - Speciel stolpe

122 mm karm - 100,2x100,2 mm.  
149 mm karm - 127,2x127,2 mm.  
175 mm karm - 153,2x153,2 mm.  
210 mm karm - 188,2x188,2 mm.

Skrueafstande og -placering som standard montage.

#### Alternative - Special post

122 mm karm - 100,2x100,2 mm.  
149 mm karm - 127,2x127,2 mm.  
175 mm karm - 153,2x153,2 mm.  
210 mm karm - 188,2x188,2 mm.

Fixing points and fixing areas as standard installation.

Alu. vinkler eller special stolpe og alu-afdækning er tilvalg.  
Øvrige montage materialer leveres af montør.

Alu. angles or special post and alu-flashing is optional.  
Other installation materials by installer.

DK Standard hjørneløsning 90°  
122/149/175/210 mm karm

[www.idealcombi.dk](http://www.idealcombi.dk)

UK Standard corner solution 90°  
122/149/175/210 mm frame

[www.idealcombi.com](http://www.idealcombi.com)

TYPE

Frame IC

Rev. no. 00

Drawing no. FRAic-HJL102

© Idealcombi A/S 2011. This material is the property of and copyright protected by IDEALCOMBI A/S.

**idealcombi**  
Udvikler vinduet