



Standard hjørne stolpe
 122 mm karm - 45x45 mm.
 149 mm karm - 60x60 mm.
 175 mm karm - 75x75 mm.
 210 mm karm - 125x125 mm.
 Opklodsning, skrueafstande og -placering som standard montage.

Standard corner post
 122 mm frame - 45x45 mm.
 149 mm frame - 60x60 mm.
 175 mm frame - 75x75 mm.
 210 mm frame - 125x125 mm.
 Wedging, fixing points and fixing areas as standard installation.

Alternativ - Speciel stolpe
 122 mm karm - 82x82 mm.
 149 mm karm - 109x109 mm.
 175 mm karm - 135x135 mm.
 210 mm karm - 170x170 mm.
 Skrueafstande og -placering som standard montage.

Alternative - Special post
 122 mm karm - 82x82 mm.
 149 mm karm - 109x109 mm.
 175 mm karm - 135x135 mm.
 210 mm karm - 170x170 mm.
 Fixing points and fixing areas as standard installation.

Alu. vinkler eller special stolpe og alu-afdækning er tilvalg.
 Øvrige montage materialer leveres af montør.

Alu. angles or special post and alu-flashing is optional.
 Other installation materials by instaler.

DK Standard hjørneløsning 90°
 122/149/175/210 mm karm med smigskæring

www.idealcombi.dk

UK Standard corner solution 90°
 122/149/175/210 bevelled frame

www.idealcombi.com

TYPE

Frame ic

Rev. no. 00

Drawing no. FRAic-HJL108

© Idealcombi A/S 2011. This material is the property of and copyright protected by IDEALCOMBI A/S.

idealcombi
 Udvikler vinduet