



Standard hjørne stolpe  
175 mm karm - 60x60 mm.  
Opklodsning, skrueafstande og -placering som standard montage.

Standard corner post  
175 mm frame - 60x60 mm.  
Wedging, fixing points and fixing areas as standard installation.

Alternativ - Speciel stolpe  
175 mm karm - 78,75x78,75 mm.  
Skrueafstande og -placering som standard montage.

Alternative - Special post  
175 mm karm - 78,75x78,75 mm.  
Fixing points and fixing areas as standard installation.

Alu. vinkler eller special stolpe og alu-afdækning er tilvalg.  
Øvrige montage materialer leveres af montør.

Alu. angles or special post and alu-flashing is optional.  
Other installation materials by instaler.

DK Standard hjørneløsning 90°  
175 mm karm med smigskøring – Skydedør

[www.idealcombi.dk](http://www.idealcombi.dk)

UK Standard corner solution 90°  
175 mm bevelled frame – Sliding door

[www.idealcombi.com](http://www.idealcombi.com)

TYPE

Futura+

Rev. no. 00

Drawing no. PLU-HJL114

© Idealcombi A/S 2011. This material is the property of and copyright protected by IDEALCOMBI A/S.

**idealcombi**  
Udvikler vinduet