

ILLMOD 600 15/7-12

OBS

Alu-afdækningen skal monteres samtidig med elementerne.

Install the alu-cover at the same time as the elements.

Hjørne stolpe: 149 mm karm - 100x100 mm.
175 mm karm - 100x100 mm.


Påforinger: 149 mm karm - PF16x110.
175 mm karm - PF16x136.

Opklodsning, skrueafstand og -placering som standard montage.

Corner post: 149 mm frame - 100x100 mm.
175 mm frame - 100x100 mm.

Packers: 149 mm frame - PF16x110.
175 mm frame - PF16x136.

Wedging, fixing points and fixing areas as standard installation.



1,5 mm bukket alu med endebuk.

Påforinger og alu-afdækning er tilvalg.
Øvrige montage materialer leveres af montør.

Packers and alu-flashing is optional.
Other installation materials by installer.

DK Standard hjørneløsning 90°
149/175 mm karm - udadgående og ondadgående

www.idealcombi.dk

UK Standard corner solution 90°
149/175 mm frame - outward opening & inward opening

www.idealcombi.com

TYPE

Futura+

Rev. no. 00

Drawing no. PLU-HJL121

© Idealcombi A/S 2011. This material is the property of and copyright protected by IDEALCOMBI A/S.

idealcombi
Udvikler vinduet